(A)] at least one homogeneously branched linear ethylene/ α -olefin interpolymer having:

(i) a density from about 0.89 grams/cubic centimeter (g/cm³) to about [0.92] 0.935 g/cm³,

(ii) a molecular weight distribution (M_W/M_n) from about 1.8 to about 2.8,

(iii) a melt index (I_2) from about 0.001 grams/10 minutes (g/10 min) to about 10 g/10 min,

(iv no [linear polymer] high density fraction, [and]

(v) a single melting peak as measured using differential scanning calorimetry[/], and

(vi) a slope of strain hardening coefficient greater than or equal to 1.3; and from about 5 percent (by weight of the total composition) to about 90 percent (by weight of the total composition) of at least one heterogeneously branched ethylene polymer having a density from about 0.93 g/cm³ to about 0.965 g/cm³.

(Amended) The film of claim, wherein the homogeneously branched linear ethylene [polymer] <u>interpolymer</u> has a slope of strain hardening coefficient greater than or equal to [about 1.3] <u>1.5</u>.

24. (Amended) [In a] An ethylene polymer composition comprising [at least one homogeneously branched ethylene/ α -olefin interpolymer and at least one heterogeneously branched ethylene/ α -olefin interpolymer, the improvement comprising incorporating into the composition] (A) from about 10 percent (by weight of the total composition) to about 95 percent (by weight of the total composition) of at least one homogeneously branched linear ethylene/ α -olefin interpolymer having:

(i) a density from about 0.89 grams/cubic centimeter (g/cm³) to about [0.92] 0.935 g/cm³,

(ii) a molecular weight distribution (M_W/M_n) from about 1.8 to about 2.8,

(iii) a melt index (\overline{l}_2) from about 0.001 grams/10 minutes (g/10 min) to about 10 g//10 min,

(iv) no [linear/polymer] high density fraction, [and]

(v) a single melting peak as measured using differential scanning calorimetry, and

(vi) a slope of strain hardening coefficient greater than or equal to 1.3; and

5/8

40121BL

(B) from about 5 percent (by weight of the total composition) to about 90 percent (by weight of the total composition) of at least one heterogeneously branched ethylene polymer having a density from about 0.93 g/cm³ to about 0.965 g/cm³.

25. (Amended) The [improvement] composition of claim 24 wherein the homogeneously branched linear ethylene/ α -olefin interpolymer has a slope of strain hardening coefficient greater than or equal to [about 1.3] 1.5.

16. (Amended) The [improvement] <u>composition</u> of claim 14 wherein the homogeneously branched linear ethylene/ α -olefin interpolymer is an interpolymer of ethylene with at least one C_3 - C_{20} α -olefin.

9/27. (Amended) The [improvement] <u>composition</u> of claim 24 wherein the homogeneously branched linear ethylene/ α -olefin interpolymer is a copolymer of ethylene and a C_3 - C_{20} α -olefin.

(Amended) The [improvement] <u>composition</u> of claim 27 wherein the homogeneously branched linear ethylene/ α -olefin interpolymer is a copolymer of ethylene and 1-octene.

29. (Amended) The [improvement] composition of claim 24 wherein the heterogeneously branched ethylene polymer is a copolymer of ethylene and a C_3 - C_{20} α -olefin.

(Amended) The [improvement] composition of claim 29 wherein the heterogeneously branched ethylene polymer is a copolymer of ethylene and 1-octene.

Please add the following new claim:

The film of Claim 9 or the composition of Claim 24, wherein the density of the at least one homogeneously branched linear ethylene/ α -olefin interpolymer is in the range from about 0.905 g/cm³ to about 0.925 g/cm³ and the I₂ melt index is in the range of from about 0.001 g/10 minutes to less than about 1 g/10 minutes.--

(p1[∞]

40121BL